





	8	7	6	5	4	3		2	1	
	SPECIFICATIONS						Produ	uct number:	A5032-15	
Н	This equipment is considered as part of a personal fall arrest system (PFAS).									Н
	It is only to be used in conjunction with a personal fall arrest system that limits the maximum arrest force (MAF) to 6,0 kN.									
G	Maximum Working Mon Horizontal Minimum Bre Vertical Minimum Break	ment (MWM) : eaking Strength : king Strength :	164 kg / User 2,1 kN•m 18,4 kN 18,0 kN	(18 625 lbf•in) (4 136 lbf) (4 407 lbf)						G
	Maximum Design Mome	ent :	24,2 kN•m	(213 980 lbf•in)			090			
F	The axle load must be equal to or greater than 1818 kgf (4 000 lbf). It is recommended to use shims to support the horizontal load of : 12 kN (2 698 lbf).									F
	STANDARDS									
	Name	Classification	Year	Users						
Е	AS / NZS 5532	Freefall arrest	2013	1						Е
	ANSI Z359.18 CSA Z259.15	D AD	2017 2017	1 1						
	OSHA 1910.140 OSHA 1926.502			1						
D	EN 795 TS 16415	Α	2012 2013	1 3						D
	MATERIAL AND CONS									
	Structure :	Stool								
С	Structure: Steel Hardware: Stainless Steel Welding certification: Steel / Stainless Steel: CSA W59.18 / CSA W47.1 and AWS D1.6 Surface finish: Finish clear zinc plated ASTM B-633-13, Type V, SC 3					PAT.NO.:				
						PRODUITS DE SERVICE PUBLICS INNOVA INC. INNOVA PUBLIC UTILITY PRODUCTS INC. © 9105-0732 QUEBEC INC. and under exclusive license to INNOVA PUBLIC UTILITY PRODUCTS INC., (hereafter « INNOVA»). All rights reserved. Protected under the Copyright Act of Canada and international treaties and agreements regarding copyrights. Violators are subject to prosecution and other legal recourses for infringement. Any reproduction, adaptation or other use or disclosure whatsoever, in totality or in part, and in any form or by any means whatsoever, strictly forbidden and requires the prior written approval of INNOVA. All data is the exclusive property of 9105-0732 QUEBEC INC. and under exclusive licenses to INNOVA and cannot be used nor disclosed in any way either without the prior written approval of INNOVA».				
	RESTRICTIONS									
В	This equipment is to be used only with products approved by Innova Public Utility Products Inc.									
	This equipment must always be operated on a level surface.						WEIGHT:	TITLE:		
	Ensure that all hardwares and connecting pins are properly installed before use.						59.3 Lb		cle Hitch System for	
Α	In the occurence of a fall or that the safety of the equipment is in doubt, the equipment must be immediately removed from service and inspected by qualified personnel before reuse.				he		26.9 Kg	Material: SH	Anchor Post EET(S): PROJET: Rev.	A
							Zinc plated	Steel	A5032-15 04	
	8	7	6	5	4	3		2	1	

